



Nitrile

## High visibility orange nitrile gloves for protection that you can see

- High visibility orange coloring
- Works exceptionally well in oily environments
- Extended cuff for added protection of wrist and forearm
- Certified by the National Fire Protection Association (NFPA)



### Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment
- Mining
- Oil and gas
- Healthcare

### Recommended For

- Inspection, selecting, checking parts
- Assembly and inspection of components
- Equipment repair and maintenance
- General Purpose Auto Aftermarket
- Sample taking and processing
- Administering drugs
- Raw material sample collection
- Picking parts and accessories
- Inspection of primary product
- Product inspection
- Vehicle maintenance
- Handling of tools
- Extra protection over the wrist and arm
- Protection from Type I latex allergy in HCW's or patients
- Extra protection over the wrist and arm
- Higher-risk clinical applications
- Protection from Type I latex allergy in HCW's or patients



## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

Blaze <sup>®</sup> N48	
<b>Material</b>	Nitrile
<b>Color</b>	Orange
<b>Glove Design</b>	Chlorinated, Powder-Free, Textured Fingers
<b>Cuff</b>	Beaded
<b>Manufacturing/QMS Audit Standards</b>	ISO 13485:2003
<b>Regulatory/Standards Compliance</b>	ASTM D6319, EN 420:2003 + A1:2009, FDA21 CFR 177-2600, NFPA 1991:2006, US QSR/FDA 510(k) Medical Examination Grade
<b>Packaging</b>	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	Malaysia
<b>User Needs Segment</b>	High Risk
<b>Available sizes</b>	S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10), XXL (10.5 - 11)

### PHYSICAL PROPERTIES

	Typical Values		Testing Method
	BEFORE AGING	AFTER AGING	
Length (mm/inches)	270 / 10.6		ASTM D3767,EN420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.13 / 5.1		ASTM D3767,EN420
Finger Thickness (mm/mils)	0.20 / 7.9		ASTM D3767,EN420
Ultimate Tensile Strength (MPa)	≥28	≥21	ASTM D412 & D573
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥9	≥10	