

Durable, extended protection

- Meets or exceeds the emergency medical glove requirements of NFPA 1999
- Thick design for added strength and durability
- Comfortable latex material for soft, elastic fit and feel
- Extended cuff for expanded protection over the wrist and forearm



Industries

- Life Sciences
- Machinery and Equipment
- Healthcare

Recommended For

- Unpacking of bulk goods
- Maintaining lab furniture and equipment
- Sample taking and processing
- Transporting raw materials
- Inspection (picking, checking and marking)
- Extra protection over the wrist and arm
- Higher-risk clinical applications



TECHNICAL DATA SHEET

PRODUCT INFORMATION

| | |
|--|--|
| | Ultra One® UL-315 |
| Material | Natural Rubber Latex |
| Color | Natural |
| Glove Design | Chlorinated, Powder-Free, Textured Fingers |
| Cuff | Beaded |
| Manufacturing/QMS Audit Standards | EN ISO 13485 : 2012 |
| Regulatory/Standards Compliance | ASTM D3578, EN 420:2003 + A1:2009, FDA21 CFR 177-2600, NFPA 1999:2013, US QSR/FDA 510(k) Medical Examination Grade |
| Packaging | 50 gloves per dispenser 10 dispensers per case 500 gloves per case |
| Storage | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition |
| Country of Origin | Malaysia |
| User Needs Segment | High Risk |

PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|---|---------------------|--------------------|---------------------|
| Length (mm/inches) | 300 / 11.8 | | ASTM D3767,EN420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/inches) | 0.25 / 9.8 | | ASTM D3767,EN420 |
| Finger Thickness (mm/inches) | 0.30 / 11.8 | | ASTM D3767,EN420 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | ≥ 32 | ≥ 20 | ASTM D412 |
| Elongation at Break (%) | ≥ 750 | ≥ 700 | ASTM D412 |

Performance Standards and Regulatory Compliance

