

Durable, extended protection

- Meets or exceeds the emergency medical glove requirements of NFPA 1999
- Thick design for added strength and durability
- Comfortable latex material for soft, elastic fit and feel
- Extended cuff for expanded protection over the wrist and forearm



Industries

- Life Sciences
- Machinery and Equipment
- Healthcare

Recommended For

- Unpacking of bulk goods
- Maintaining lab furniture and equipment
- Sample taking and processing
- Transporting raw materials
- Inspection (picking, checking and marking)
- Extra protection over the wrist and arm
- Higher-risk clinical applications



TECHNICAL DATA SHEET

PRODUCT INFORMATION

	Ultra One[®] UL-315
Material	Natural Rubber Latex
Color	Natural
Glove Design	Chlorinated, Powder-Free, Textured Fingers
Cuff	Beaded
Manufacturing/QMS Audit Standards	EN ISO 13485 : 2012
Regulatory/Standards Compliance	ASTM D3578, EN 420:2003 + A1:2009, FDA21 CFR 177-2600, NFPA 1999:2013, US QSR/FDA 510(k) Medical Examination Grade
Packaging	50 gloves per dispenser 10 dispensers per case 500 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition
Country of Origin	Malaysia
User Needs Segment	High Risk

PHYSICAL PROPERTIES

	Typical Values		Testing Method
	BEFORE AGING	AFTER AGING	
Length (mm/inches)	300 / 11.8		ASTM D3767,EN420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/inches)	0.25 / 9.8		ASTM D3767,EN420
Finger Thickness (mm/inches)	0.30 / 11.8		ASTM D3767,EN420
Ultimate Tensile Strength (MPa)	≥ 32	≥ 20	ASTM D412 & D573
Elongation at Break (%)	≥ 750	≥ 700	ASTM D412