

Sili-Thane™ 803 Sealant

PTY340 For Build-A-Berm Barrier, Metals, Masonry, Glass, Plastics & Wood,6 per box

Polyether-based adhesive offers superior sealing properties and flexibility.

- Excellent for creating flexible, liquidtight seals when used with our PIG Build-A-Berm products
- Adheres to aluminum, brass, steel, stainless steel, concrete, brick, stone, glass, ceramic tile, fiberglass, ABS, PVC, polyester, plywood and more
- Provides superior UV resistance, flexibility and a 30-minute, tack-free cure time
- Resistant to mild solvents, hydrocarbons and oils for worry-free use in industrial applications
- Sealant maintains structural integrity in high humidity; won't foam or bubble when applied



Volume

Sold as

Weight

per Pallet

Distributor Part Number

Item#	Description	Dimensions	Weight
PTY340-BK		ext. dia. 2" x 11.25" H	7.65 lbs.
PTY340-WH		ext. dia. 2" x 11.25" H	7.65 lbs.
Metric Equivalent:			
Item#	Description	Dimensions	Weight
PTY340-BK		ext. dia. 5.1cm x 28.6cm H	3.5 kg
PTY340-WH		ext. dia. 5.1cm x 28.6cm H	3.5 kg
Specifications			
Use With		Build-A-Berm Barrier, Metals, Wood	Masonry, Glass, Plastics &
Dimensions		ext. dia. 2" x 11.25" H	
Brand		Polymeric	
Repair Type		Permanent	
Temperature Limit		-40°F (-40°C) to 195°F (90°C	

10.3 fl. oz. Cartridge

6 per box

7.65 lbs.

250

45gp05;45gp06;7014146;5046281;04088x00242

Composition	Polyether-Based Adhesive
Shelf Life	1 year
UNSPSC	31201606
Pigalog® Page Number	Page 155

Metric Equivalent

Dimensions	ext. dia. 5.1cm x 28.6cm H
Weight	3.5 kg

Technical Information

CountryShipOnly

This product can ONLY be shipped to: United States, Chile, Colombia, French Polynesia.

Technical Documents

Sili-Thane™ 803 Sealant

Sili-Thane 803 Sealant (White)

Silithane 803 Black Sealant