

## Intrinsically Safe Dual-Light™ Lantern

### Rechargeable



The XPR-5580 Intrinsically Safe Dual-Light™ Lantern is a Flashlight, a Floodlight and a Dual-Light that is cULus, ATEX, and IECEx certified intrinsically safe. The flashlight and floodlight offers 3 user-selectable brightness settings. The flashlight beam is perfect for cutting through smoke and lighting up objects at great distances. The 30 lumens "Survival Mode" provides just enough light in an emergency situation with a run-time of 65 hrs. The Dual-Light mode allows the user to simultaneously see objects at a distance, as well as, see the ground in front of them as they walk or work. The 5580 is powered by a single rechargeable Lithium-ion battery.

**INTRINSICALLY SAFE**



**210** Flashlight Lumens  
**200** Floodlight Lumens  
**300** Dual-Light™ Lumens



- cULus, ATEX, and IECEx listed Intrinsically Safe
- Flashlight/Floodlight/Dual-Light™
- User-selectable brightness settings on Flashlight & Floodlight including a 30 Lumen Survival mode on Floodlight
- Meets the requirements for NFPA-1971-8.6 (2013)
- Charger meets requirements of NFPA-1901 (2009)




**XPR 5580R**

### Intrinsically Safe Dual-Light™ Lantern Rechargeable

#### FEATURES

- cULus, ATEX, and IECEx certified Intrinsically Safe
- CREE® LED technology – 50,000 + hours LED life
- Flashlight/Floodlight/Dual-Light™
- 3 User-selectable brightness settings on the flashlight plus a strobe
- High-efficiency deep parabolic reflector creating a sharp focused flashlight beam
- 3 User-selectable brightness setting on the floodlight including a 30 Lumen Survival Mode
- Dual-light (both the flashlight & floodlight on at the same time) provides for maximum lighting versatility and user safety
- Glass-filled Nylon Polymer housing
- Dual body switches
- Dustproof / Waterproof
- Impact & chemical resistant
- Light meets the requirements of NFPA-1971-8.6 (2013)
- Charger meets the requirements of NFPA-1901 (2009)
- Serialized for personal identification
- Powered by rechargeable Lithium-ion battery (included)
- Limited Lifetime Warranty

3 User-selectable brightness setting on the Floodlight including a 30 Lumen Survival Mode



3 User-selectable brightness settings on the Flashlight



High-Efficiency Deep Parabolic Reflector



Wall or vehicle mounted charger



Rear-Facing Green Safety LED

#### SPECIFICATIONS

- Lumens: flashlight high-210, medium-100, low-30, floodlight high-200, medium 100, survival 30, Dual-Light-300
- Run-time: flashlight high-12.5 hrs, medium-19.5 hrs, low- 65 hrs, floodlight high-14 hrs, medium-19.5 hrs, survival-65 hrs, Dual-Light-9.25 hrs
- Recharge time: 6 hours
- Beam distance: 635 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 8in, width: 4.75in, height: 5.5in, bezel diameter: 4.75 in, weight: 33oz

FL1 STANDARD	HIGH	MEDIUM	LOW
	210 LUMENS	100 LUMENS	30 LUMENS
	12h 30m	19h 30m	65h
	635m	257m	164m
	101,000cd	16,515cd	6,705cd
	2m		
	1m		

#### INCLUDED

- Light
- Rechargeable Lithium-ion Battery
- Wall or Vehicle Mounted Charger
- Shoulder Strap
- AC & DC Power Supplies



#### SAFETY RATING

Model	UPC 0 17398
XPR-5580R	80596 4

## XPR-5580

### Intrinsically Safe Dual-Light™ Lantern - Rechargeable

**MARKET APPLICATIONS**

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

**DESCRIPTION**

The XPR-5580 Intrinsically Safe Dual-Light™ Lantern is a Flashlight, a Floodlight and a Dual-Light that is cULus, ATEX, and IECEx certified intrinsically safe. The flashlight and floodlight offers 3 user-selectable brightness settings. The flashlight beam is perfect for cutting through smoke and lighting up objects at great distances. The 30 lumens “Survival Mode” provides just enough light in an emergency situation with a run-time of 65 hrs. The Dual-Light mode allows the user to simultaneously see objects at a distance, as well as, see the ground in front of them as they walk or work. The 5580 is powered by a single rechargeable Lithium-ion battery.

**CASE MATERIAL**

Glass-filled Nylon Polymer Housing

**DIMENSIONS**

Length: 8 in • Width: 4.75 in • Height: 5.5 in • Bezel Diameter: 4.75 in

**WEIGHT**

Weight: 33 oz

**LENS**

Unbreakable polycarbonate with scratch resistant coating

**LIGHT SOURCE**

Flashlight: CREE® LED with a 50,000 hour lifetime

**LIGHT OUTPUT**

Flashlight: 210 lumens, Floodlight: 210 lumens, Dual-Light: 300 lumens

**ON/OFF**

Dual Body Switch - Flashlight: High, Medium, Low and Floodlight: High, Medium, Survival

**RUN-TIME**

Flashlight: High: 12.5 hours, Medium: 19.5, Low: 65, Floodlight: High: 14 hours, Medium: 19.5, Survival: 65

**BATTERY**







Li-ion battery pack (included)

**FEATURES**

- cULus, ATEX, and IECEx certified Intrinsically Safe
- CREE LED technology – 50,000+ hours LED life
- Flashlight/Floodlight/Dual-Light™
- 3 brightness settings on the Flashlight
- High-efficiency deep parabolic reflector
- 3 brightness setting on the Floodlight including a 30 Lumen Survival Mode
- Glass-filled Nylon Polymer housing
- Dual body switches
- Dustproof / Waterproof
- Impact & chemical resistant
- Meets requirements of NFPA-1971-8.6 (2013)
- Charger meets requirements of NFPA-1901 (2009)
- Serialized for personal identification
- Powered by rechargeable Li-ion battery (included)
- Upgradeable to 40 hrs. of run-time
- Limited Lifetime Warranty

**WARRANTY**

Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

FL1 STANDARD	HIGH	MEDIUM	LOW
	210 LUMENS	100 LUMENS	30 LUMENS
	12h 30m	19h 30m	65h
	635m	257m	164m
	101,000cd	16,515cd	6,705cd
	2m		
	1m		

