

100 Series Autoranging Automotive Multimeter

3505A



The 3505A is the latest version of the Classic 100 Series Autoranging Automotive Multimeter with many new and useful troubleshooting features. It still features all of the same basic Multimeter functions plus some new and powerful Automotive specific test functions.

Features:

- Auto/Manual Ranging
- Resistance, Continuity, Diode and Capacitance Tests
- RPM Measurement
- Temperature Measurement (°F/°C)
- Millisecond Pulse width and Peak Volts measurements for Fuel Injectors
- Duty Cycle and Frequency to 10M Hz
- Dwell Measurement
- O2 Cross counts
- Relative Measurement, can be used for low resistance measurements to remove test lead resistance from measurement
- Data Recording: Min/Max for fluctuating measurements
- Data Hold, freeze data at the push of a button
- Fused direct current measurement up to 10 amps through meter
- Auto Power Off (can be disabled)

Specifications:

- DC Voltage: 400mV/4/40/400V±0.5%, 600V±0.8%
- AC Voltage: 4/40/400V±0.8%, 400mV/600V±1.2%
- DC Current: 40/400mA±1.5%, 4/10A±2%
- AC Current: 40/400mA±2%, 4/10A±2.5%
- Resistance: 400Ω/4/40/400kΩ±1%, 4/40MΩ±2%
- Capacitance: 40nF/400nF/4μF /40μF±3%, 400μF /4000μF±20%
- Frequency: 1Hz -10MHz±0.1%
- Duty Cycle: 0.1%-99.9%±2%
- FI PEAK Voltages: 4/40/400V±5%
- O2 CROSS COUNT: 0 – 500Hz (per second)±0.5%
- RPM: 0 – 10000 RPM±0.5%
- Dwell Angle: 1 – 12 CYL±2%
- Pulse Width-ms (Negative):1~999ms±2%
- Temperature: -50°C - +400°C±0.75%±3°C /-58°F - +752°F±0.75%±5°F



No. 3505A – Includes: 100 Series Automotive Multimeter, heavy-duty test leads with removable alligator clip ends, inductive RPM clamp, temperature probe.

09-05 ©2009 SPX. All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials, and specifications without notice. Certain kits may require additional cables or adapters. Product shipped may differ from photo(s) shown.



Learn more about automotive tools we have.