



SPECIFICATION SHEET

34-874



MAXIFLEX® ULTIMATE™ SEAMLESS KNIT NYLON / LYCRA® GLOVE WITH NITRILE COATED MICRO-FOAM GRIP

- Micro-Foam Nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Knit Wrist helps prevent dirt and debris from entering the glove
- 100% Silicone-free
- Patented micro-foam nitrile coating offers 360° breathability,
- 25% thinner than most foam nitrile gloves on the market
- Mimics the "hand at rest", reducing hand fatigue & increasing comfort
- The micro-cup finish allows for a controlled and optimized grip
- CFIA Approved
- Complies with FDA food handling requirements 21 CFR, Part 177

APPLICATIONS

- General assembly
- Micro-engineering
- Automotive components
- Painting
- Horticulture

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

| | | | | | | | | |
|-------------|--------------------------------------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| MATERIAL | Seamless nylon with Lycra® liner; micro-foam nitrile coating | | | | | | | |
| COLOR | ■ Black / Gray | | | | | | | |
| CUFF STYLE | Continuous Knit | | | | | | | |
| SIZES | XXS-XXXL | | | | | | | |
| PACKAGING | 12 pair per dozen, 12 dozen per case | | | | | | | |
| CASE | 19.7" x 11.6" x 10.6" / 50cm x 29.5cm x 27cm | | | | | | | |
| CASE WEIGHT | XXS | XS | S | M | L | XL | XXL | XXXL |
| | 11.2 lbs 5.1 kg | 11.9 lbs 5.4 kg | 13.2 lbs 6.0 kg | 15.0 lbs 6.8 kg | 15.7 lbs 7.1 kg | 16.3 lbs 7.4 kg | 17.0 lbs 7.7 kg | 18.1 lbs 8.2 kg |
| COO | Sri Lanka | | | | | | | |

PERFORMANCE PROPERTIES

| | | | | | | |
|-------------|--------------------------------------------------------------|---|---|---|---|---|
| EN388: 4131 | ASTM F2992-15 ANSI Cut Level A1 (Adopted by ANSI/ISEA 02/16) | | | | | |
| | ASTM F1790-05 ANSI Cut Level 1 | | | | | |
| ABRASION | 0 | 1 | 2 | 3 | 4 | - |
| CUT | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | - |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | - |



BARCODES

| ITEM | PAIR | DOZEN | CASE |
|---------------|------|----------------|----------------|
| ■ 34-874/XXS | --- | 01616314020346 | 02616314020346 |
| ■ 34-874/XS | --- | 01616314017940 | 02616314017940 |
| ■ 34-874/S | --- | 01616314017957 | 02616314017957 |
| ■ 34-874/M | --- | 01616314017964 | 02616314017964 |
| ■ 34-874/L | --- | 01616314017971 | 02616314017971 |
| ■ 34-874/XL | --- | 01616314017988 | 02616314017988 |
| ■ 34-874/XXL | --- | 01616314066060 | 02616314066069 |
| ■ 34-874/XXXL | --- | 01616314125767 | 02616314125766 |

DIMENSIONS (in/cm)

| | XXS | XS | S | M | L | XL | XXL | XXXL |
|----------|------------|------------|------------|------------|------------|------------|------------|------------|
| A | 7.3 / 18.5 | 7.7 / 19.5 | 8.1 / 20.5 | 8.5 / 21.5 | 8.7 / 22.0 | 8.9 / 22.5 | 9.1 / 23.0 | 9.4 / 24 |
| B | 3.0 / 7.5 | 3.1 / 8.0 | 3.2 / 8.2 | 3.3 / 8.4 | 3.7 / 9.4 | 3.8 / 9.7 | 3.9 / 10.0 | 4.1 / 10.5 |
| H | ■ Purple | ■ Blue | □ White | ■ Green | ■ Brown | ■ Yellow | ■ Grey | ■ Magenta |

