



PIT-PAL PRODUCTS

**THANK YOU FOR CHOOSING PIT PAL PRODUCTS!
YOUR PURCHASE IS GREATLY APPRECIATED!**

**Please continue to choose Pit Pals, the Industry Leader
for all your organizational needs in the trailer, shop or at the track!**

INSTALLATION INSTRUCTIONS FOR SLICK MOUNTS PART #282

Pit Pals has developed a new concept in a wall or trailer mounted tire rack. It features a unique telescoping design to fit almost any backspace wheel dimension. It is crafted of heavy duty 14 gauge 1 1/2" square by 48" long steel tubing. .125 steel round clamping plates secured by 5/8" x 3 1/2" coarse thread clamping knobs hold wheels firmly. Black powdercoat finish. Set of 2.

INSTALLATION ON TRAILER WALL

CAUTION: When mounting tire, BE SURE FRONT OF TIRE RIM IS FACING YOU! Trim Lock will prevent scratches on surface of rim. Mounting tire rim backwards will make metal-to-metal contact and will likely cause damage to the front rim finish.

Front of Rim.

Trim Lock

Once tire is mounted and backspace is established, collar is tightened w/allen-head to stabilize mounting.

Bolt

Optional hole drilled through and bolted to further stabilize mounted wheel.

Bolt

Because of the extremely heavy load bearing characteristics of this unit, it is very important to mount it securely into a reinforcing rib of the trailer wall, using customer provided 1" x 5/16" coarse thread mounting screws.

If rib mounting is not possible, it is recommended drilling through the wall, using the proper length 5/16" coarse thread carriage bolts, nuts and washers to mount the unit from the outer wall.

Form No.282 Rev 6/00