

**NEW**

# 1/4" FLEXAIR hybrid polymer hose with pressed metal sleeves, non-scratch sheath and prevoS1 quick safety couplings



### Technical characteristics

**Operating pressure:** 29 to 174 psi

**Temperature:** +5°F to +140°F

**Construction:** PVC

**Equipped with:** Coupler and adapter

ID (in)	Coupler	Plug	Length (ft)	Parts Numbers
1/4"	ISI 06	IRP 06	25'	<b>RST RISB1425</b>
1/4"	ISI 06	IRP 06	50'	<b>RST RISB1450</b>
1/4"	ISI 06	IRP 06	100'	<b>RST RISB14100</b>
1/4"	USI 06	URP 06	25'	<b>RST RUSB1425</b>
1/4"	USI 06	URP 06	50'	<b>RST RUSB1450</b>
1/4"	USI 06	URP 06	100'	<b>RST RUSB14100</b>
1/4"	ESI 07	ERP 07	25'	<b>RST RESB1425</b>
1/4"	ESI 07	ERP 07	50'	<b>RST RESB1450</b>
1/4"	ESI 07	ERP 07	100'	<b>RST RESB14100</b>
1/4"	ASI 06	ARP 06	25'	<b>RST RASB1425</b>
1/4"	ASI 06	ARP 06	50'	<b>RST RASB1450</b>
1/4"	ASI 06	ARP 06	100'	<b>RST RASB14100</b>