

Compact, Versatile Reels | Series 4000 / 5000 / 5005

Made in USA 



4625 OLP


5635 OLP

5650 OLP

Premium Duty Spring Retractable Reels

Air/Water/Oil/Grease - 1/4", 3/8", 1/2" I.D.

Series 4000, 5000, and 5005 reels are all-steel construction and compact for a wide range of applications with critical space requirements. A full flow shaft and swivel assures maximum product delivery. Guide arm adjusts to two positions.


	Dimensions - Size Index							
	1		2		3		4	
	in	mm	in	mm	in	mm	in	mm
A	12 ⁷ / ₈	327	14 ³ / ₈	365	17 ⁵ / ₈	448	17 ⁵ / ₈	448
B	12 ⁵ / ₈	321	14 ¹ / ₄	362	16 ³ / ₄	425	16 ³ / ₄	425
C	8	203	9 ³ / ₄	248	9 ³ / ₄	248	9 ³ / ₄	248
D	2 ¹ / ₂	64	2 ¹ / ₂	64	2 ¹ / ₂	64	2 ¹ / ₂	64
E	5 ⁵ / ₈	143	6 ¹ / ₈	156	5 ⁷ / ₈	149	7 ¹ / ₄	184





































NOTE: See operating instructions for optimum mounting configuration.



Side Mount Reels
4625 OLP SML

Air Vend Reels
AV4425 OLPBWR



Quiet latch with Hose	Ratchet latch with Hose	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		**Max Pressure	NPT(M) Hose Outlet	NPT(F) Reel Inlet	Quiet latch without hose or bumper	Shipping Weight		Pressure	Size Index #		
		lbs	kg	in	mm	in	mm	ft	m	psi	bar	in		in	lbs			kg	psi
Low Pressure Air/Water Reels Maximum temperature 150 °F (65 °C) w/hose / 210 °F (99 °C) w/o hose **Maximum working pressure at 70 °F (20 °C)																			
4420 OLP 	-----	18	8	1/4	6	.475	12	20	6	300	21	1/4	3/8	4400 OLP  	17	8	500	35	1
4425 OLP  	B4425 OLP	19	9	1/4	6	.475	12	25	8	300	21	1/4	3/8	4400 OLP  	17	8	500	35	1
4435 OLP  	B4435 OLP	19	9	1/4	6	.475	12	35	11	300	21	1/4	3/8	4400 OLP  	17	8	500	35	1
5450 OLP  	B5450 OLP	26	12	1/4	6	.475	12	50	15	300	21	1/4	3/8	5400 OLP  	20	9	500	35	2
4617 OLP	-----	19	9	3/8	10	.600	15	17	5	300	21	1/4	3/8	4600 OLP  	17	8	500	35	1
4625 OLP  	B4625 OLP	20	9	3/8	10	.600	15	25	8	300	21	1/4	3/8	4600 OLP  	17	8	500	35	1
5635 OLP  	B5635 OLP	25	11	3/8	10	.600	15	35	11	300	21	1/4	3/8	5600 OLP  	21	10	500	35	2
5650 OLP  	B5650 OLP	36	16	3/8	10	.600	15	50	15	300	21	1/4	3/8	5605 OLP  	31	14	500	35	3
A5825 OLP  	B5825 OLP	27	12	1/2	13	.750	19	25	8	300	21	1/2	3/8	A5800 OLP	22	10	500	35	2
A5835 OLP  	B5835 OLP	39	18	1/2	13	.750	19	35	11	300	21	1/2	3/8	A5805 OLP	32	15	500	35	3
A5850 OLP  	B5850 OLP	41	19	1/2	13	.750	19	50	15	300	21	1/2	3/8	A5806 OLP	35	16	500	35	4
Medium Pressure Oil Reels Maximum temperature 210 °F (99 °C)																			
5435 OMP	B5435 OMP	31	14	1/4	6	.530	13	35	11	2750	190	1/4	3/8	5400 OMP	23	10	3000	207	2
5630 OMP	B5630 OMP	31	14	3/8	10	.690	18	30	9	2600	179	3/8	3/8	5600 OMP 	24	11	3000	207	2
A5825 OMP*	B5825 OMP*	34	15	1/2	13	.820	21	25	8	3000	207	1/2	3/8	A5800 OMP	24	11	3000	207	2
A5835 OMP	B5835 OMP	42	19	1/2	13	.820	21	35	11	3000	207	1/2	3/8	A5805 OMP	32	15	3000	207	3
High Pressure Grease Reels Maximum temperature 210 °F (99 °C)																			
5430 OHP	-----	30	14	1/4	6	.580	15	30	9	5000	345	1/4	1/4	5400 OHP	23	10	5000	345	2
5435 OHP	B5435 OHP	39	18	1/4	6	.580	15	35	11	5000	345	1/4	1/4	5405 OHP	33	15	5000	345	3
5625 OHP	B5625 OHP	32	15	3/8	10	.730	19	25	8	4800	331	1/4	1/4	5600 OHP	26	12	5000	345	2

*Floor tank mount only - do not mount on ceiling. Low pressure reels furnished standard with PVC hose. Compressed air hoses should not be converted to oxygen service - may cause explosion when O₂ mixes with fuel. Medium pressure reels furnished standard with S.A.E. 100R1-AT (1/4" and 3/8") or S.A.E. 100R17 (1/2") one wire braid hose. High pressure reels furnished standard with S.A.E. 100 R2T two wire braid hose. Reference page 6 for guide arm positions.