




## MINIMATCH

03.5650/03.5650AU/03.5650UK/03.5650US



2 COLOUR LIGHT - 2 step

### Operating

Press and hold button

2 sec to change CCT.

Releasing button will save the CCT setting



Ultra high CRI+  
COB LED



250/500 lux @0.5m  
(step 1/2)



100/200 lumen  
(step 1/2)



4500/6500K



CRI 96+



3.7V/1600 mAh  
Li-ion



4h/2h  
(step 1/2)



4h



-10° to +40° C



IP65



156x60x38 mm



190 g

Above specifications apply to the work light only




Incl. CHARGER  
Input: 100-240V AC 50/60Hz  
Output: 5V DC 1A



# MINIMATCH

## BATTERY TREATMENT / WARNING

- During charging, the  will indicate the level of charge in red color. When fully charged, all 4 led bars will light up in green color
- Don't leave battery flat. Otherwise it could be over discharged and may NOT be able to be reused
- If lamp will be stored for one month or more, please fully charge it prior to storage
- Always replace the battery with a new one of the same type and grade
- Opening the lamp is not advisable, as doing so could contribute to the lamp no longer being water-tight
- Avoid looking directly into the beam, as it will dazzle
- Don't use the lamp near open flames
- When the lamp is turned off, press and hold the power button for 3 seconds to display battery charge status in the indicator



Discarded electrical products must not be disposed of together with household waste. Please use recycling facilities. Ask your local authority or retailer for advice on recycling.

- The battery must be removed from the device before it is broken up
- The device must be disconnected from the mains when the battery is removed
- Please dispose of the battery safely