




## SUNMATCH 3

03.5651/03.5651AU/03.5651UK/03.5651US



ALL DAYLIGHT - 5 step

### Operating

Press and hold button to change between the 5 different colour temperatures (2500K-6500K)



To save battery and avoid risk of overheating an intelligent built-in system switches turn the lamp to low mode after 3 minutes use at high mode.



Ultra high CRI+  
COB LED  
Spot: High power LED



700/1400 lux @0.5m  
(step 1/2)  
Spot: 5000 lux@0.5m



250/500 lumen  
(step 1/2)  
Spot: 200 lumen



2500K/3500K/4500K  
/5500K/6500K  
Spot: 4000K



CRI 96+  
Spot: 95 CRI



3.7V/2600 mAh  
Li-ion



2h  
Spot: 3h



4h



-10° to +40° C



IP65

Above specifications apply to the work light only



190x60x38 mm



270 g



Incl. CHARGER  
Input: 100-240V AC 50/60Hz  
Output: 5V DC 1A



Work light specifications

## SUNMATCH 3

### BATTERY TREATMENT / WARNING

- During charging, the 4 led bars will indicate the level of charge in red color. When fully charged, all 4 led bars will light up with green color
- Don't leave battery flat. Otherwise it could be over discharged and may NOT be able to be reused
- If lamp will be stored for one month or more, please fully charge it prior to storage
- Always replace the battery with a new one of the same type and grade
- Opening the lamp is not advisable, as doing so could contribute to the lamp no longer being water-tight
- Avoid looking directly into the beam, as it will dazzle
- Don't use the lamp near open flames
- When the lamp is turned off, press and hold the power button for 3 seconds to display battery charge status in the indicator



Discarded electrical products must not be disposed of together with household waste. Please use recycling facilities. Ask your local authority or retailer for advice on recycling.

- The battery must be removed from the device before it is broken up
- The device must be disconnected from the mains when the battery is removed
- Please dispose of the battery safely