

## 1 Identification

- **Product identifier**
- **Trade name:** *2800 Series Low VOC Rust Shield*
- **Article number:**  
28061, 28064, 28081, 28091, 28094, 28101, 28104, 28111, 28114, 28121, 28131, 28134, 28141, 28151, 28154, 28161, 28164, 28171, 28181, 28191, 28194, 2810-DR
- **Application of the substance / the mixture** *Coating*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*SEM Products Inc.*

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



*GHS02 Flame*

*Flam. Liq. 2 H225 Highly flammable liquid and vapor.*



*GHS08 Health hazard*

*Muta. 1B H340 May cause genetic defects.*

*Carc. 1A H350 May cause cancer.*

*Repr. 2 H361 Suspected of damaging fertility or the unborn child.*

*STOT SE 2 H371 May cause damage to organs.*

*STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.*



*GHS07*

*Skin Irrit. 2 H315 Causes skin irritation.*

*Eye Irrit. 2A H319 Causes serious eye irritation.*

*STOT SE 3 H335 May cause respiratory irritation.*

- **Label elements**

- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*

(Contd. on page 2)

Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Alkyd Resin  
Quartz (SiO<sub>2</sub>)  
toluene  
Stoddard solvent

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H371 May cause damage to organs.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P264 Wash thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P321 Specific treatment (see on this label).  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P314 Get medical advice/attention if you feel unwell.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**  
Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

	Alkyd Resin	30-40%
14807-96-6	Talc	13-30%
67-64-1	acetone	10-13%
107-87-9	pentan-2-one	≥7-<10%
1330-20-7	xylene	5-7%
14808-60-7	Quartz (SiO <sub>2</sub> )	1.5-5%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	1.5-5%
64742-95-6	Solvent naphtha (petroleum), light aromatic	1.5-5%
1333-86-4	Carbon black	1.5-5%
108-88-3	toluene	1.5-5%
111-76-2	2-butoxyethanol	1-1.5%
112926-00-8	precipitated Silica (Silica-Amorphous)	1-1.5%
8052-41-3	Stoddard solvent	≥0.1-≤1%
100-41-4	ethylbenzene	≥0.1-≤1%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)



Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 3)

- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

67-64-1	acetone	200 ppm
107-87-9	pentan-2-one	150 ppm
1330-20-7	xylene	130 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
108-88-3	toluene	67 ppm
111-76-2	2-butoxyethanol	60 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm
8052-41-3	Stoddard solvent	300 mg/m <sup>3</sup>
95-63-6	1,2,4-trimethylbenzene	140 ppm
108-67-8	mesitylene	140 ppm
67-56-1	methanol	530 ppm

(Contd. on page 5)



Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 4)

100-41-4	ethylbenzene	33 ppm
96-29-7	2-butanone oxime	30 ppm
111-77-3	2-(2-methoxyethoxy)ethanol	3.4 ppm
98-82-8	cumene	50 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
149-57-5	2-ethylhexanoic acid	15 mg/m <sup>3</sup>

· PAC-2:

67-64-1	acetone	3200* ppm
107-87-9	pentan-2-one	830 ppm
1330-20-7	xylene	920* ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
108-88-3	toluene	560 ppm
111-76-2	2-butoxyethanol	120 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	200 ppm
8052-41-3	Stoddard solvent	1,800 mg/m <sup>3</sup>
95-63-6	1,2,4-trimethylbenzene	360 ppm
108-67-8	mesitylene	360 ppm
67-56-1	methanol	2,100 ppm
100-41-4	ethylbenzene	1100* ppm
96-29-7	2-butanone oxime	56 ppm
111-77-3	2-(2-methoxyethoxy)ethanol	37 ppm
98-82-8	cumene	300 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m <sup>3</sup>

· PAC-3:

67-64-1	acetone	5700* ppm
107-87-9	pentan-2-one	5000* ppm
1330-20-7	xylene	2500* ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
108-88-3	toluene	3700* ppm
111-76-2	2-butoxyethanol	700 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	1,200 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	3000* ppm
8052-41-3	Stoddard solvent	29500** mg/m <sup>3</sup>
95-63-6	1,2,4-trimethylbenzene	480 ppm
108-67-8	mesitylene	480 ppm
67-56-1	methanol	7200* ppm
100-41-4	ethylbenzene	1800* ppm

(Contd. on page 6)



**Trade name: 2800 Series Low VOC Rust Shield**

(Contd. of page 5)

96-29-7	2-butanone oxime	250 ppm
111-77-3	2-(2-methoxyethoxy)ethanol	220 ppm
98-82-8	cumene	730 ppm
107-98-2	1-methoxy-2-propanol	660 ppm
149-57-5	2-ethylhexanoic acid	590 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
BEI	

### 107-87-9 pentan-2-one

PEL	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 530 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 529 mg/m <sup>3</sup> , 150 ppm

(Contd. on page 7)



Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 6)

**1330-20-7 xylene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
 REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
 TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
 BEI

**14808-60-7 Quartz (SiO<sub>2</sub>)**

PEL Long-term value: 0.05\* mg/m<sup>3</sup>  
 \*resp. dust; 30mg/m<sup>3</sup>/%SiO<sub>2</sub>+2  
 REL Long-term value: 0.05\* mg/m<sup>3</sup>  
 \*respirable dust; See Pocket Guide App. A  
 TLV Long-term value: 0.025\* mg/m<sup>3</sup>  
 \*as respirable fraction

**1333-86-4 Carbon black**

PEL Long-term value: 3.5 mg/m<sup>3</sup>  
 REL Long-term value: 3.5\* mg/m<sup>3</sup>  
 \*0.1 in presence of PAHs; See Pocket Guide Apps.A+C  
 TLV Long-term value: 3\* mg/m<sup>3</sup>  
 \*inhalable fraction

**108-88-3 toluene**

PEL Long-term value: 200 ppm  
 Ceiling limit value: 300; 500\* ppm  
 \*10-min peak per 8-hr shift  
 REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
 TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
 BEI

**111-76-2 2-butoxyethanol**

PEL Long-term value: 240 mg/m<sup>3</sup>, 50 ppm  
 Skin  
 REL Long-term value: 24 mg/m<sup>3</sup>, 5 ppm  
 Skin  
 TLV Long-term value: 97 mg/m<sup>3</sup>, 20 ppm  
 BEI

**112926-00-8 precipitated Silica (Silica-Amorphous)**

PEL 20mppcf or 80mg/m<sup>3</sup> /%SiO<sub>2</sub>  
 REL Long-term value: 6 mg/m<sup>3</sup>  
 See Pocket Guide App. C  
 TLV TLV withdrawn

**8052-41-3 Stoddard solvent**

PEL Long-term value: 2900 mg/m<sup>3</sup>, 500 ppm  
 REL Long-term value: 350 mg/m<sup>3</sup>  
 Ceiling limit value: 1800\* mg/m<sup>3</sup>  
 \*15-min

(Contd. on page 8)



Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 7)

TLV	Long-term value: 525 mg/m <sup>3</sup> , 100 ppm
<b>100-41-4 ethylbenzene</b>	
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI
<b>Ingredients with biological limit values:</b>	
<b>67-64-1 acetone</b>	
BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
<b>1330-20-7 xylene</b>	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
<b>108-88-3 toluene</b>	
BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene  0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene  0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)
<b>111-76-2 2-butoxyethanol</b>	
BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
<b>100-41-4 ethylbenzene</b>	
BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)  - Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

(Contd. on page 9)





Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 8)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55.8-56.6 °C

(Contd. on page 10)



Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 9)

· <b>Flash point:</b>	-18 °C
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	465 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
· <b>Explosion limits:</b>	
<b>Lower:</b>	2.6 Vol %
<b>Upper:</b>	13 Vol %
· <b>Vapor pressure at 20 °C:</b>	233 hPa
· <b>Density at 20 °C:</b>	1.06495 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	39.9 %
<b>Water:</b>	0.0 %
<b>VOC content:</b>	23.15 %
	309.0 g/l / 2.58 lb/gal
<b>Solids content:</b>	59.4 %
· <b>Other information</b>	No further relevant information available.

## \* 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 11)



Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 10)

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
The product can cause inheritable damage.

· **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
14807-96-6	Talc	3
1330-20-7	xylene	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
1333-86-4	Carbon black	2B
108-88-3	toluene	3
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B
98-82-8	cumene	2B
· <b>NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
98-82-8	cumene	R
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
68911-87-5	montmorilontie clay complex	

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 12)





Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 11)

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b>	UN1263
· <b>DOT, ADR, IMDG, IATA</b>	
· <b>UN proper shipping name</b>	Paint
· <b>DOT</b>	1263 Paint, special provision 640D
· <b>ADR</b>	PAINT
· <b>IMDG, IATA</b>	
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>ADR, IMDG, IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	II
· <b>DOT, ADR, IMDG, IATA</b>	
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>EMS Number:</b>	F-E, <u>S-E</u>
· <b>Stowage Category</b>	B
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.

(Contd. on page 13)


**Trade name: 2800 Series Low VOC Rust Shield**

(Contd. of page 12)

**· Transport/Additional information:**
**· DOT**
**· Quantity limitations**
*On passenger aircraft/rail: 5 L*
*On cargo aircraft only: 60 L*
**· ADR**
**· Excepted quantities (EQ)**
*Code: E2*
*Maximum net quantity per inner packaging: 30 ml*
*Maximum net quantity per outer packaging: 500 ml*
**· IMDG**
**· Limited quantities (LQ)**
*5L*
**· Excepted quantities (EQ)**
*Code: E2*
*Maximum net quantity per inner packaging: 30 ml*
*Maximum net quantity per outer packaging: 500 ml*
**· UN "Model Regulation":**
*UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II*
**15 Regulatory information**
**· Safety, health and environmental regulations/legislation specific for the substance or mixture**
**· Sara**
**· Section 355 (extremely hazardous substances):**
*None of the ingredient is listed.*
**· Section 313 (Specific toxic chemical listings):**

14807-96-6 Talc

1330-20-7 xylene

Acrylic Resin

108-88-3 toluene

111-76-2 2-butoxyethanol

95-63-6 1,2,4-trimethylbenzene

67-56-1 methanol

100-41-4 ethylbenzene

COBALT CARBOXYLATE

111-77-3 2-(2-methoxyethoxy)ethanol

98-82-8 cumene

**· TSCA (Toxic Substances Control Act):**

14807-96-6 Talc

67-64-1 acetone

107-87-9 pentan-2-one

1330-20-7 xylene

 14808-60-7 Quartz (SiO<sub>2</sub>)

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

1333-86-4 Carbon black

108-88-3 toluene

(Contd. on page 14)



Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 13)

111-76-2	2-butoxyethanol
68911-87-5	montmorilontie clay complex
123-86-4	n-butyl acetate
8052-41-3	Stoddard solvent
95-63-6	1,2,4-trimethylbenzene
108-67-8	mesitylene
67-56-1	methanol
100-41-4	ethylbenzene
96-29-7	2-butanone oxime
111-77-3	2-(2-methoxyethoxy)ethanol
98-82-8	cumene
107-98-2	1-methoxy-2-propanol
149-57-5	2-ethylhexanoic acid
7732-18-5	water

· **TSCA new (21st Century Act) (Substances not listed)**

	Alkyd Resin
64742-95-6	Solvent naphtha (petroleum), light aromatic
112926-00-8	precipitated Silica (Silica-Amorphous)

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO <sub>2</sub> )
1333-86-4	Carbon black
95-63-6	1,2,4-trimethylbenzene
100-41-4	ethylbenzene
98-82-8	cumene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
67-56-1	methanol

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
108-88-3	toluene	II
111-76-2	2-butoxyethanol	NL
95-63-6	1,2,4-trimethylbenzene	II
108-67-8	mesitylene	II
100-41-4	ethylbenzene	D

(Contd. on page 15)

Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 14)

98-82-8	cumene	D, CBD
· <b>TLV (Threshold Limit Value established by ACGIH)</b>		
14807-96-6	Talc	A4
67-64-1	acetone	A4
1330-20-7	xylene	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
1333-86-4	Carbon black	A4
108-88-3	toluene	A4
111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	
1333-86-4	Carbon black	
67-56-1	methanol	

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Danger

- **Hazard-determining components of labeling:**

Alkyd Resin  
Quartz (SiO<sub>2</sub>)  
toluene  
Stoddard solvent

- **Hazard statements**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H371 May cause damage to organs.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.

(Contd. on page 16)



Trade name: 2800 Series Low VOC Rust Shield

(Contd. of page 15)

- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P321 Specific treatment (see on this label).
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Rita Joiner

· **Date of preparation / last revision** 10/23/2018 / 8

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

(Contd. on page 17)





Version number 9

**Trade name: 2800 Series Low VOC Rust Shield**

(Contd. of page 16)

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

*Muta. 1B: Germ cell mutagenicity – Category 1B*

*Carc. 1A: Carcinogenicity – Category 1A*

*Repr. 2: Reproductive toxicity – Category 2*

*STOT SE 2: Specific target organ toxicity (single exposure) – Category 2*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

· **\* Data compared to the previous version altered.**

USA