



RUST PREVENTER CAVITY WAX

TECHNICAL DATA SHEET



Check local VOC regulations to ensure compliance of all products in your area.

DESCRIPTION

Rust Preventer Cavity Wax is a semi-transparent black internal panel compound to restore OEM corrosion protection on inner body panels and cavities.

FEATURES

- OEM recommended
- Non-hardening
- Sprayable in 360° pattern
- Superior adhesion
- Fast drying
- Excellent corrosion protection
- Superior wicking

SUITABLE SUBSTRATES

- Inner body panels, cavities, and channels

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
39573	Rust Preventer Cavity Wax	Semi-transparent Black	20 oz. Aerosol
39574	Rust Preventer Cavity Wax	Semi-transparent Black	Quart

	39573	39574
Regulatory VOC:	N/A	3.58 #/gal (430 g/L)
Actual VOC:	N/A	3.53 #/gal (424 g/L)
MIR:	Category ABT .812	N/A
Paintable:	No	No

HANDLING AND APPLICATION

PREPARATION:

Clean any accessible areas with **SEM Solve** or **XXX Universal Surface Cleaner** and wipe dry.

APPLICATION:

RUST PREVENTER AEROSOL

Shake can for 1 minute prior to use. Remove cap, attach straw or **Rust Preventer Aero Wand**.

RUST PREVENTER AEROSOL + AERO WAND



Check local VOC regulations to ensure compliance of all products in your area.

Apply 1-2 coats. Change the angle of the **Aero Wand**, and vary the depth of the wand inside the panel to ensure complete coverage. Clean **Aero Wand** by attaching the tip and wand to **XXX Universal Gun Cleaner** or solvent compliant with VOC regulations in your area.

Note:

With the **Rust Preventer Aero Wand** attached, the spray pattern is 360°, do not spray product without tip being inserted into inner panel access point.

RUST PREVENTER QUART + PREMIUM UNDERCOAT GUN AND WAND

Shake bottle for 1 minute prior to use, remove cap. Attach **Rust Preventer** to **Premium Undercoat Gun & Wand**.

Note:

With the **Premium Undercoat Gun & Wand** attached, the spray pattern is 360°, do not spray product without tip being inserted into inner panel access point.

Using 35-40 psi, apply 1-2 coats changing the angle of the gun, and varying the depth of the tip inside the panel to ensure complete coverage. Clean wand with **XXX Universal Gun Cleaner** or solvent compliant with VOC regulations in your area.

STORAGE:

Rust Preventer should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **Rust Preventer** is 3 years when stored under normal conditions.

RELATED PRODUCTS:

Part:	Product Name:	Size:
38371	SEM Solve	Gallon
38373	SEM Solve	20 oz. Aerosol
38374	SEM Solve	Quart
38375	SEM Solve	5 Gallon
71110	Premium Undercoat Gun & Wand	Each
71120	Rust Preventer Aero Wand	Each
77763	XXX Universal Gun Cleaner	20 oz. Aerosol
77771	XXX Universal Surface Cleaner	Gallon
77774	XXX Universal Surface Cleaner	Quart