



1 Identification

- **Product identifier**
- **Trade name:** 45501, 45504, 45508 **Rust Trap Black**
- **Article number:** 45501, 45504, 45508
- **Application of the substance / the mixture** Coating

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08



Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 1)

· **Signal word** Danger

· **Hazard-determining components of labeling:**

POLYMERIC MDI

Solvent naphtha (petroleum), light arom.

Aromatic Polyisocyanate

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate, isomeres and homologues

methylenediphenyl diisocyanate

· **Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

(Contd. on page 3)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 2)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 2
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 2
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.

Weight percentages

· **Dangerous components:**

53862-89-8	POLYMERIC MDI	30 - 40%
64742-95-6	Solvent naphtha (petroleum), light arom.	13 - 30%
127821-00-5	Aromatic Polyisocyanate	7 - 10%
101-68-8	4,4'-methylenediphenyl diisocyanate	5 - 7%
95-63-6	1,2,4-trimethylbenzene	5 - 7%
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	1.5 - 5%
108-67-8	mesitylene	1.5 - 5%
165101-57-5	Mono-Oxazolidine	1.5 - 5%
26447-40-5	methylenediphenyl diisocyanate	1-1.5%
98-82-8	cumene	≤1%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	≤1%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m ³
95-63-6	1,2,4-trimethylbenzene	140 ppm
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	0.15 mg/m ³
108-67-8	mesitylene	140 ppm
26447-40-5	methylenediphenyl diisocyanate	29 mg/m ³
1333-86-4	Carbon black	9 mg/m ³
1330-20-7	xylene	130 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
98-82-8	cumene	50 ppm
584-84-9	4-methyl-m-phenylene diisocyanate	0.020 ppm

· PAC-2:

101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m ³
95-63-6	1,2,4-trimethylbenzene	360 ppm

(Contd. on page 5)



Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 4)

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3.6 mg/m ³
108-67-8	mesitylene	360 ppm
26447-40-5	methylenediphenyl diisocyanate	40 mg/m ³
1333-86-4	Carbon black	99 mg/m ³
1330-20-7	xylene	920* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
98-82-8	cumene	300 ppm
584-84-9	4-methyl-m-phenylene diisocyanate	0.083 ppm

· **PAC-3:**

101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m ³
95-63-6	1,2,4-trimethylbenzene	480 ppm
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	22 mg/m ³
108-67-8	mesitylene	480 ppm
26447-40-5	methylenediphenyl diisocyanate	240 mg/m ³
1333-86-4	Carbon black	590 mg/m ³
1330-20-7	xylene	2500* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
98-82-8	cumene	730 ppm
584-84-9	4-methyl-m-phenylene diisocyanate	0.51 ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 6)



Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 5)

At this time, the other constituents have no known exposure limits.

101-68-8 4,4'-methylenediphenyl diisocyanate	
PEL	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV	Long-term value: 0.051 mg/m ³ , 0.005 ppm
95-63-6 1,2,4-trimethylbenzene	
REL	Long-term value: 125 mg/m ³ , 25 ppm
TLV	Long-term value: 123 mg/m ³ , 25 ppm
108-67-8 mesitylene	
REL	Long-term value: 125 mg/m ³ , 25 ppm
TLV	Long-term value: 123 mg/m ³ , 25 ppm
98-82-8 cumene	
PEL	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV	Long-term value: (246) NIC-0.5 mg/m ³ , (50) NIC-0.1 ppm NIC-A2

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Liquid

Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

162 °C

· Flash point:

45 °C

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

450 °C

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower:

0.7 Vol %

Upper:

7.5 Vol %

· Vapor pressure at 20 °C:

5 hPa

· Density at 20 °C:

1.03415 g/cm³

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:

Not determined.

Kinematic:

Not determined.

· Solvent content:

Organic solvents:

31.8 %

(Contd. on page 8)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 7)

VOC content:	31.8 % 328.5 g/l / 2.74 lb/gl
Solids content:	68.4 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
101-68-8 4,4'-methylenediphenyl diisocyanate		
Oral	LD50	2200 mg/kg (mouse)
95-63-6 1,2,4-trimethylbenzene		
Oral	LD50	5000 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
101-68-8	4,4'-methylenediphenyl diisocyanate	3
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3
1333-86-4	Carbon black	2B

(Contd. on page 9)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 8)

1330-20-7	xylene	3
98-82-8	cumene	2B

· **NTP (National Toxicology Program)**

98-82-8	cumene	R
584-84-9	4-methyl-m-phenylene diisocyanate	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information





· UN-Number	
· DOT, ADR, IMDG, IATA	UN1993
· UN proper shipping name	
· DOT	Flammable liquids, n.o.s. (Solvent naphtha (petroleum), light arom., 1,2,4-trimethylbenzene)
· ADR	1993 Flammable liquids, n.o.s. (Solvent naphtha (petroleum), light arom., 1,2,4-trimethylbenzene), special provision 640E
· IMDG	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom., 1,2,4-trimethylbenzene, 1,3,5-TRIMETHYLBENZENE, ISOPROPYLBENZENE)

(Contd. on page 10)



Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 9)

· IATA	<i>FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom., 1,2,4-trimethylbenzene)</i>
· Transport hazard class(es)	
· DOT	
	
· Class	<i>3 Flammable liquids</i>
· Label	<i>3</i>
<hr/>	
· ADR, IMDG	
 	
· Class	<i>3 Flammable liquids</i>
· Label	<i>3</i>
<hr/>	
· IATA	
	
· Class	<i>3 Flammable liquids</i>
· Label	<i>3</i>
· Packing group	
· DOT, ADR, IMDG, IATA	<i>III</i>
· Environmental hazards:	<i>Product contains environmentally hazardous substances: Aromatic Polyisocyanate</i>
· Marine pollutant:	<i>Yes</i>
	<i>Symbol (fish and tree)</i>
· Special marking (ADR):	<i>Symbol (fish and tree)</i>
· Special precautions for user	<i>Warning: Flammable liquids</i>
· EMS Number:	<i>F-E,<u>S-E</u></i>
· Stowage Category	<i>A</i>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	<i>Not applicable.</i>
· Transport/Additional information:	
· DOT	
· Quantity limitations	<i>On passenger aircraft/rail: 60 L</i> <i>On cargo aircraft only: 220 L</i>
<hr/>	
· ADR	
· Excepted quantities (EQ)	<i>Code: E1</i> <i>Maximum net quantity per inner packaging: 30 ml</i> <i>Maximum net quantity per outer packaging: 1000 ml</i>

(Contd. on page 11)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 10)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S., SPECIAL PROVISION 640E (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM., 1,2,4-TRIMETHYLBENZENE), 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

584-84-9	4-methyl-m-phenylene diisocyanate
----------	-----------------------------------

· **Section 313 (Specific toxic chemical listings):**

101-68-8	4,4'-methylenediphenyl diisocyanate
----------	-------------------------------------

95-63-6	1,2,4-trimethylbenzene
---------	------------------------

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
-----------	--

	Acrylic Resin
--	---------------

26447-40-5	methylenediphenyl diisocyanate
------------	--------------------------------

1330-20-7	xylene
-----------	--------

98-82-8	cumene
---------	--------

584-84-9	4-methyl-m-phenylene diisocyanate
----------	-----------------------------------

· **TSCA (Toxic Substances Control Act):**

53862-89-8	POLYMERIC MDI
------------	---------------

64742-95-6	Solvent naphtha (petroleum), light arom.
------------	--

9017-27-0	Alpha-methyl styrene/vinyl toluene copolymer
-----------	--

127821-00-5	Aromatic Polyisocyanate
-------------	-------------------------

101-68-8	4,4'-methylenediphenyl diisocyanate
----------	-------------------------------------

95-63-6	1,2,4-trimethylbenzene
---------	------------------------

9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
-----------	--

108-67-8	mesitylene
----------	------------

165101-57-5	Mono-Oxazolidine
-------------	------------------

26447-40-5	methylenediphenyl diisocyanate
------------	--------------------------------

1333-86-4	Carbon black
-----------	--------------

1330-20-7	xylene
-----------	--------

108-83-8	2,6-dimethylheptan-4-one
----------	--------------------------

98-82-8	cumene
---------	--------

64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
------------	--

584-84-9	4-methyl-m-phenylene diisocyanate
----------	-----------------------------------

(Contd. on page 12)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 11)

· **Proposition 65**

· **Chemicals known to cause cancer:**

95-63-6	1,2,4-trimethylbenzene
1333-86-4	Carbon black
1330-20-7	xylene
98-82-8	cumene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
95-63-6	1,2,4-trimethylbenzene	II
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	CBD
108-67-8	mesitylene	II
1330-20-7	xylene	I
98-82-8	cumene	D, CBD

· **TLV (Threshold Limit Value established by ACGIH)**

1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
584-84-9	4-methyl-m-phenylene diisocyanate	(A4)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
584-84-9	4-methyl-m-phenylene diisocyanate

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

POLYMERIC MDI

Solvent naphtha (petroleum), light arom.

Aromatic Polyisocyanate

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate, isomeres and homologues

methylenediphenyl diisocyanate

· **Hazard statements**

H226 Flammable liquid and vapor.

(Contd. on page 13)



Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 12)

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

(Contd. on page 14)



Printing date 06/28/2017

Reviewed on 06/28/2017

Trade name: 45501, 45504, 45508 Rust Trap Black

(Contd. of page 13)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Date of preparation / last revision** 06/28/2017 / 9

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

USA