



## 1 Identification

- **Product identifier**
- **Trade name:** 69501,69508 Rust Mort
- **Article number:** 69501, 69508, 69504
- **Application of the substance / the mixture** Coating

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
phosphoric acid
- **Hazard statements**  
H314 Causes severe skin burns and eye damage.
- **Precautionary statements**  
P260 Do not breathe dusts or mists.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).



Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 69501,69508 Rust Mort

(Contd. of page 1)

- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:  
Mixture: consisting of the following components.  
Weight percentages

- Dangerous components:

|         |             |          |
|---------|-------------|----------|
| 67-63-0 | propan-2-ol | 1.5 - 5% |
|---------|-------------|----------|

### 4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

### 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 69501,69508 Rust Mort

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

|         |             |         |
|---------|-------------|---------|
| 67-63-0 | propan-2-ol | 400 ppm |
|---------|-------------|---------|

### · PAC-2:

|         |             |           |
|---------|-------------|-----------|
| 67-63-0 | propan-2-ol | 2000* ppm |
|---------|-------------|-----------|

### · PAC-3:

|         |             |             |
|---------|-------------|-------------|
| 67-63-0 | propan-2-ol | 12000** ppm |
|---------|-------------|-------------|

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)



Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 69501,69508 Rust Mort

(Contd. of page 3)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**67-63-0 propan-2-ol**

|     |  |
|-----|--|
| PEL | Long-term value: 980 mg/m <sup>3</sup> , 400 ppm   |
| REL | Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 980 mg/m <sup>3</sup> , 400 ppm |
| TLV | Short-term value: 984 mg/m <sup>3</sup> , 400 ppm<br>Long-term value: 492 mg/m <sup>3</sup> , 200 ppm  |
| BEI |  |

· **Ingredients with biological limit values:**

**67-63-0 propan-2-ol**

|     |   |
|-----|---|
| BEI | 40 mg/L<br>Medium: urine<br>Time: end of shift at end of workweek<br>Parameter: Acetone (background, nonspecific) |
|-----|---|

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 69501,69508 Rust Mort

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:

Liquid

Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

100 °C

· Flash point:

100 °C

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product does not present an explosion hazard.  
In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower:

Not determined.

Upper:

Not determined.

· Vapor pressure at 20 °C:

23 hPa

· Density at 20 °C:

1.18364 g/cm<sup>3</sup>

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

Water:

Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:

Not determined.

Kinematic:

Not determined.

· Solvent content:

Organic solvents:

3.2 %

(Contd. on page 6)



Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 69501,69508 Rust Mort

(Contd. of page 5)

**Water:** 51.6 %  
**VOC content:** 3.2 %  
0.0 g/l / 0.00 lb/gl

**Solids content:** 0.3 %  
**Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**  
Strong caustic effect.  
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Corrosive  
Irritant  
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|         |             |   |
|---------|-------------|---|
| 67-63-0 | propan-2-ol | 3 |
|---------|-------------|---|

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)



Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 69501,69508 Rust Mort

(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

### 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1760
- **UN proper shipping name**
- **DOT** Corrosive liquids, n.o.s. (Phosphoric acid solution)
- **ADR** 1760 Corrosive liquids, n.o.s. (Phosphoric acid solution)
- **IMDG, IATA** CORROSIVE LIQUID, N.O.S. (PHOSPHORIC ACID, SOLUTION)
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 8 Corrosive substances
- **Label** 8
- **ADR, IMDG, IATA**
- 
- **Class** 8 Corrosive substances
- **Label** 8

(Contd. on page 8)



Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 69501,69508 Rust Mort

(Contd. of page 7)

|   |  |
|---|--|
| · Packing group<br>· DOT, ADR, IMDG, IATA   | III  |
| · Environmental hazards:<br>· Marine pollutant:   | No   |
| · Special precautions for user<br>· EMS Number:<br>· Segregation groups<br>· Stowage Category<br>· Stowage Code | Warning: Corrosive substances<br>F-A,S-B<br>Acids<br>A<br>SW2 Clear of living quarters.                                |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code                                       | Not applicable.  |
| · Transport/Additional information:<br>· DOT<br>· Quantity limitations  | On passenger aircraft/rail: 5 L<br>On cargo aircraft only: 60 L  |
| · ADR<br>· Excepted quantities (EQ)   | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml       |
| · IMDG<br>· Limited quantities (LQ)<br>· Excepted quantities (EQ)   | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation":  | UN 1760 CORROSIVE LIQUIDS, N.O.S. (PHOSPHORIC ACID SOLUTION), 8, III   |

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

### · Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

### · TSCA (Toxic Substances Control Act):

67-63-0 propan-2-ol

7732-18-5 water

### · Proposition 65

#### · Chemicals known to cause cancer:

None of the ingredients is listed.

#### · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 9)





Printing date 06/28/2017

Reviewed on 06/20/2017

Trade name: 69501,69508 Rust Mort

(Contd. of page 8)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

67-63-0 propan-2-ol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05

· **Signal word** Danger

· **Hazard-determining components of labeling:**

phosphoric acid

· **Hazard statements**

H314 Causes severe skin burns and eye damage.

· **Precautionary statements**

P260 Do not breathe dusts or mists.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

(Contd. on page 10)



Printing date 06/28/2017

Reviewed on 06/20/2017

**Trade name: 69501,69508 Rust Mort**

(Contd. of page 9)

· **Date of preparation / last revision 06/28/2017 / 9**

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

· **\* Data compared to the previous version altered.**

USA