

TERA PUMP

BATTERY POWERED
FUEL TRANSFER

MODEL: TREP01

TRANSFER MADE EASY



TRANSFERS
2.5 GAL/MIN

BATTERY
POWERED

FLOW CONTROL
NOZZLE

SPECIFICATIONS



Rigid Intake: 15.0"
Flexible Outtake: 39.4"
Pump Head: 8.7"
Intake Width: 1.2"

Compatible Liquids	Gasoline Diesel Antifreeze Kerosene
-----------------------	--

FLOW CONTROL NOZZLE & COMPATIBILITY

Our Flow Control Nozzle enables complete control of transfer flow from quick stops to low and high flow!

The TREP01 can also transfer various fuel and liquids from gasoline to kerosene!



CSA SAFETY CERTIFIED

The Tera Pump TREP01 is officially certified and rigorously tested by the CSA Group.

This assures that our product's handling of electronics and gasoline are absolutely safe to use according to the high standards of ANSI, UL, CSA, and NSF.

HOW TO USE



1 INSERT INTAKE
INTO GAS CAN



2 INSERT NOZZLE
INTO FUEL TANK



3 SWITCH ON &
LET IT FLOW

Features

- Flow Rate of up to 2.4 Gallons per Minute
- Discharge Hose Holder: Built-in nozzle holder for safe and convenient way of storing the discharge nozzle
- Big Slide Switch: Big On/Off Switch
- U-Shaped battery compartment: U-shaped hook for easier storage
- Flexible Discharge Hose & Intake Hose

Flow Control Nozzle

- Control the rate of liquid at any moment by squeezing the Nozzle lever
- Lower Level Position for Refueling
- Upper lever position for watering

Swivel Connection

- Nozzle connection is able to perform a 360 degree rotation to prevent hose from tangling

Filter Attachment

- Filter-equipped intake end protects the pumping system from damage due to foreign debris
- Filters are made from stainless steel mesh

Power

- 2 x D Battery Powered, Sold Separately

Compatible Liquids

- Gasoline, diesel, DEF (AdBlue), non-potable water, kerosene, antifreeze, windshield washer fluid, mild detergents, agricultural chemicals & light oils

Warranty

- Backed by a 1-Year Manufacturers Warranty