

# TECHNICAL DATA SHEET

PRODUCT: *BASE COAT / CLEAR COAT (EXTRA)*

**BASE COAT /  
CLEAR COAT  
(EXTRA)**



## DESCRIPTION:

What's the 'Extra'? We took the original Base Coat / Clear Coat lightweight body repair formula and added self-leveling technology to reduce sanding. Base Coat / Clear Coat Extra has a smooth creamy texture that delivers easy spreading and extra adhesion to galvanized, zinc-treated and aluminum surfaces, and is stain free, tack free and clog free.

## PART NUMBERS:

- 16060 Base Coat/Clear Coat Extra Gallon 4 gal / case 35 lbs / case

## PRODUCT USES:

Use for filling and repair of minor bodywork up to ¼", such as dents, dings, hail damage and small holes.

## TYPICAL SUBSTRATES:

- Steel
- Aluminum
- Fiberglass
- Body Filler
- Wood
- 2K Primers
- Aged, sanded OEM Topcoats
- Galvanized and other zinc-coated steel
- SMC – can be used for cosmetic repairs. For structural repairs prone to high degrees of stress and flexibility, use an SMC repair product.



## SURFACE PREPARATION:

1. Clean surface. Remove all dirt, oil, grease and wax with a cleaning solvent such as #1240-1 Wax, Grease & Silicone Remover.
2. Make sure surface is dry before repairing.
3. Use 40-80 grit disc to featheredge paint for good mechanical adhesion.



## MIXING:

For best results, bring filler and provided hardener to room temperature (minimum temperature 75°F). Stir product before dispensing with a bottom to top motion. Knead hardener tube before use. Place a 4" diameter puddle of filler on a clean mixing surface (we recommend a non-absorbent plastic mixing board) and add a ribbon of cream hardener from edge to edge across the center of the filler puddle (puddles larger than 4" will require additional hardener); or measure hardener at 2% by weight of filler – a 50 to 1 ratio. Mix thoroughly with a plastic spreader, using a folding motion, until uniform color is achieved. At room temperature (75°F) approximate setting time is 3 – 5 minutes.

## APPLICATION:

1. Using a plastic spreader, apply a thin layer of filler to surface, using firm pressure for maximum adhesion.
2. Apply additional layers, if necessary, building up damaged area higher than surrounding metal surface to allow for sanding of filler.
3. **IMPORTANT! DO NOT RETURN UNUSED MIXTURE TO CAN AS IT WILL HARDEN THE REMAINING CONTENTS.**

**FINISHING:**

1. When material has cured, in approximately 15 minutes, sand with a 80-120 grit sandpaper.
2. Finish sand with 180-240 grit.

**TOPCOATING:**

May be topcoated with polyester, 2K urethane or 1K primer. Refer to paint manufacturer’s instructions for topcoat application.

**SPECIAL NOTES:**

May be intermixed with PRO-GLAZE™, BLAZE GLAZE™, or Icing® or thinned with SUPER CHARGER™.



**TECHNICAL INFORMATION (as mixed with Cream Hardener @ 2%):**

Appearance:	Yellow-Gold
VOC	Packaged: 225 g/l
	Applied: 0.8 g/l
Weight Per Gallon (Density):	9.9 pounds (Average)
Viscosity @ 77°F	82,000 cps (Average)
Gel Time @ 77°F:	3.0 – 4.0 minutes
Shore “D” Hardness Values @ 24 hours:	55-60 minutes
Sanding Time @ 77°F:	15-20 minutes
Maximum Heat Resistance:	200° for 30 minutes
Maximum Heat:	200° F for 30 minutes
Catalyst Required:	Benzoyl Peroxide
Catalyzation Ratio:	2% by weight
Exotherm Temperature:	210°F (Average)
Tack Free Time:	10 – 15 minutes

**ASSOCIATED MSDS:** Filler: “Base Coat/Clear Coat Extra 16060”

Hardener: “Cream Hardener”



**HEALTH & SAFETY:**

Read all warnings, first aid and safety for all components before using. Keep out of reach of children and animals. Protect hands with impervious rubber gloves. Wear face, skin and eye protection. When sanding, we recommend the use of a respiratory covering device to protect from dust (MSA mask P/N 459029 with MSA cartridge 464029 or equivalent). When using power equipment, refer to power tool manufacturer’s recommendations for safety equipment. USC products are for industrial use by trained professionals only.



## SAFETY DATA SHEET

### Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**Product identifier**

**Product Code** 16060.G01

**Product Name** BC/CC EXTRA GAL

**Other means of identification**

No information available

**Recommended use of the chemical and restrictions on use**

Fillers and putty

**Details of the supplier of the safety data sheet**

*See section 16 for more information*

### Section 2: HAZARDS IDENTIFICATION

**Classification**

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

**Label elements**



Signal word

**DANGER**

#### HAZARD STATEMENTS

Flammable liquid and vapor

Causes skin irritation

Causes serious eye irritation

May cause cancer

Suspected of damaging fertility or the unborn child

Causes damage to the following organs through prolonged or repeated exposure: Ears

#### PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### RESPONSE

IF exposed or concerned: Get medical advice/attention.

##### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### Skin

If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

##### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

##### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

##### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep cool.

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

#### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

#### OTHER HAZARDS

Not applicable.

**UNKNOWN ACUTE TOXICITY** .0001% of the mixture consists of ingredient(s) of unknown toxicity.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
---------------	--------	----------

Styrene	100-42-5	10 - 25
Titanium dioxide	13463-67-7	0.3 - 1
N,N-Dimethylaniline	121-69-7	0.1 - 0.3

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## Section 4: FIRST AID MEASURES

### **First Aid Measures**

#### **General advice**

IF exposed or concerned: Get medical advice/attention.

#### **Eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin Contact**

If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### **Inhalation**

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

#### **Ingestion**

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

### **Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

### **Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

### **Suitable extinguishing media**

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

### **Specific hazards arising from the chemical**

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

### **Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## Section 6: ACCIDENTAL RELEASE MEASURES

### **Personal precautions, protective equipment and emergency procedures**

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### **For emergency responders**

Use personal protection recommended in Section 8.

### **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### **Methods and material for containment and cleaning up**

#### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

## **Section 7: HANDLING AND STORAGE**

### **Precautions for safe handling**

#### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

#### **General Hygiene Considerations**

Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep tightly closed in a dry and cool place.

#### **Incompatible materials**

Strong bases. Strong oxidizing agents. Strong acids. Acids. Alkali. Aluminum.

## **Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Control parameters**

#### **Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

<b>Chemical Name</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>	<b>NIOSH IDLH</b>
Styrene 100-42-5	STEL: 40 ppm TWA: 20 ppm	TWA: 100 ppm Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m <sup>3</sup> STEL: 100 ppm STEL: 425 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
N,N-Dimethylaniline 121-69-7	STEL: 10 ppm TWA: 5 ppm S*	TWA: 5 ppm TWA: 25 mg/m <sup>3</sup> S*	IDLH: 100 ppm TWA: 5 ppm TWA: 25 mg/m <sup>3</sup> STEL: 10 ppm STEL: 50 mg/m <sup>3</sup>

### **Appropriate engineering controls**

#### **Engineering Controls**

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

## **Individual protection measures, such as personal protective equipment**

### **Eye/face protection**

Wear safety glasses with side shields (or goggles).

### **Skin and body protection**

Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

### **Hand Protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

### **Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

### **Thermal Protection**

No information available

## **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

### **Information on basic physical and chemical properties**

<b>Physical state</b>	Paste/Gel
<b>Appearance</b>	No information available
<b>Odor</b>	Aromatic
<b>Color</b>	dark yellow
<b>Odor Threshold</b>	No information available
<b>pH value</b>	No information available
<b>Melting point/freezing point</b>	No information available
<b>Boiling point / boiling range</b>	No information available °C / °F
<b>flash point</b>	32 °C / 90 °F
<b>evaporation rate</b>	No information available
<b>Flammability (solid, gas)</b>	No information available
<b>Flammability Limit in Air</b>	
<b>Upper flammability limit:</b>	No information available
<b>Lower flammability limit:</b>	No information available
<b>Vapor Pressure</b>	No information available
<b>vapor density</b>	No information available
<b>Density (lbs per US gallon)</b>	9.83
<b>specific gravity</b>	1.18
<b>Solubility(ies)</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	32300 mm <sup>2</sup> per second
<b>Dynamic viscosity</b>	No information available

### **Other information**

## **Section 10: STABILITY AND REACTIVITY**

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.

**Hazardous polymerization** None under normal processing.

**Conditions to avoid** Heat, flames and sparks.

**Incompatible materials** Strong bases. Strong oxidizing agents. Strong acids. Acids. Alkali. Aluminum.

**Hazardous Decomposition Products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Hydrocarbons.

## Section 11: TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Eye contact**

Causes serious eye irritation

**Skin Contact**

Causes skin irritation

**Ingestion**

Not applicable

**Inhalation**

Not applicable

### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene 100-42-5	= 1000 mg/kg ( Rat )	-	= 11.7 mg/L ( Rat ) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
N,N-Dimethylaniline 121-69-7	= 951 mg/kg ( Rat )	= 1770 µL/kg ( Rabbit )	> 0.5 - 5.0 mg/L ( Rat ) 4 h

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 48639 Mg/kg  
**ATEmix (dermal)** 145918 Mg/kg  
**ATEmix (inhalation-dust/mist)** 8.2 mg/l  
**ATEmix (inhalation-vapor)** 59 mg/l

**UNKNOWN ACUTE TOXICITY** .0001% of the mixture consists of ingredient(s) of unknown toxicity.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Styrene 100-42-5		Group 2B	Reasonably Anticipated	X
Titanium dioxide 13463-67-7		Group 2B		X

*IARC (International Agency for Research on Cancer)*

*Group 2B - Possibly Carcinogenic to Humans.*

*NTP (National Toxicology Program)*

*Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen.*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present.*

**Skin corrosion/irritation** Causes skin irritation

**Serious eye damage/eye irritation** Causes serious eye irritation

**Skin sensitization** Not applicable

**Respiratory sensitization** Not applicable

**Germ cell mutagenicity** Not applicable

**Carcinogenicity** May cause cancer



**Reproductive Toxicity** Suspected of damaging fertility or the unborn child  
**Specific target organ toxicity (single exposure)** Not applicable  
**Specific target organ toxicity (repeated exposure)**  
 Causes damage to the following organs through prolonged or repeated exposure: Ears  
**Aspiration hazard** Not applicable

## Section 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Environmental precautions Prevent product from entering drains.

### Persistence and degradability

No information available

### Bioaccumulation

No information available

### Mobility

No information available

### Other adverse effects

No information available

## Section 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

## Section 14: TRANSPORT INFORMATION

	<u>DOT</u>	<u>IMDG</u>	<u>IATA</u>
<b>14.1 UN/ID no</b>	UN1866	UN1866	UN1866
<b>14.2 Proper shipping name</b>	Resin solution	Resin solution	Resin solution
<b>14.3 Hazard Class</b>	3	3	3
<b>14.4 Packing Group</b>	III	III	III
<b>14.5 Environmental hazard</b>			
<b>14.6 Special Provisions</b>	B1, B52, IB3, T2, TP1	223, 955	A3
	<b>Emergency Response Guide Number</b>	<b>EmS-No</b>	
	127	F-E, S-E	
<b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>			No information available

*The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.*

## Section 15: REGULATORY INFORMATION

### International Inventories

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing.

**DSL** - Canadian Domestic Substances List

Not all components are listed or exempt from listing

### US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Styrene 100-42-5 10 - 25	0.1		Present
N,N-Dimethylaniline 121-69-7 0.1 - 0.3	1		Present

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb			X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
N,N-Dimethylaniline 121-69-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

## US State Regulations

### Rule 66 status of product

Not photochemically reactive.

### California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer.

### U.S. EPA Label information

EPA Pesticide registration number Not applicable

### U.S. State Right-to-Know Regulations

Chemical Name
Proprietary Inert
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Styrene 100-42-5
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Magnesium carbonate 546-93-0
Carbonic acid, calcium salt (1:1) 471-34-1
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Proprietary Inert
N,N-Dimethylaniline 121-69-7

## Section 16: OTHER INFORMATION

### HMIS

Health hazards 3\*

\* = Chronic Health Hazard

Flammability 3

Physical hazards 1

Personal Protection X

### Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet

Learn more about paint and body repair we have.