



- Soldering Bath
- WSB 150 Soldering Bath 150 W, 24 V
- Connectable to all Weller 150 W digital stations and WR3M
- For tin coating and preparation of electronics components and leads
- Precision temperature control / 150° F - 850° F / 50° C - 454° C
- Heated surface - 150 W: Soldering bath - 2.3" x 1.2" x 0.75" / 58 mm x 30 mm x 19 mm
- For lead free solder
- Heat-up time ~ 10 min (50°C - 350°C)
- For lead free solder

WSB 150 Soldering bath

Product no.: T0052704299N

| | |
|--|--------------------|
| Dimensions L x W x H (mm) | 175 x 120 x 54 |
| Dimensions L x W x H (inches) | 6.89 x 4.72 x 2.13 |
| Weight (approx.) in kg | --- |
| Voltage | 24 V |
| Power | 150 W |
| Channels | --- |
| Temperature range (depends on tool) °C | 66 - 454 |
| Temperature range (depends on tool) °F | 150 - 850 |
| Temperature accuracy °C | --- |
| Temperature accuracy °F | --- |
| Temperature accuracy for hot air °C | --- |
| Temperature accuracy for hot air °F | --- |
| Temperature stability °C | --- |
| Temperature stability °F | --- |
| Equipotential bonding socket | --- |
| Display | --- |
| Additional vacuum pump | --- |
| Max. hot air flow rate l/min (depends on tool) | --- |
| Capacity l/min | --- |
| Max. vacuum | --- |
| Interface | --- |