EF5500DE/D



EF5500DE



EF5500D

TOP FEATURES:

- **1.** Reduced price, more wattage Great value with the same legendary quality and performance.
- **2.** The EF5500DE comes with an electric starter and auto choke for effortless push button starting.
- ${f 3}$. Comes standard with wheels, fold-down/locking handles and battery.
- 4. Eight hours run time at full load -13% longer run time than previous model.
- **5.** Digital Hour Meter, Digital Volt Meter displays total run time accumulation for servicing and indicates the voltage output.
- ${\bf 6.}$ 3 year industrial and residential warranty with optional Y.E.S. for customer peace of mind.
- 7. Lifting eye convenient for hoisting and security.
- **8**. OHV engine offers efficiency, increased reliability, and quieter operation.
- **9.** Full power, full time 120/240 dual voltage is ideal for the job site or home backup.
- **10.** Ground Fault Circuit Interruption (GFCI) senses a leak to ground to reduce risk of electric shock.
- **11**. Fuel gauge provides easy monitoring of fuel level.
- **12.** The EF5500D/DE features a rugged design with full roll cage protection for heavy jobs.



EF5500DE/D

FEATURES & BENEFITS

FEATURES:

New and improved OHV MZ360 engine with a hemispherical head

- Yamaha legendary durability and reliability

Rugged Wheel kit w/fold-down locking handles — Standard on EF5500DE and EF5500D

The battery is standard on the EF5500DE — Wheel kit and Battery are a great value and offer added convenience for transport and starting

Cast iron cylinder lining — Optimal heat dissipation

Automatic oil warning system shuts off engine before oil level is low — Prevents engine damage, avoids costly repairs, minimizes down time, enhances long term durability

Transistorized ignition provides lean, efficient spark — Maintenance-free and ensures fast, easy starting, reliable operation

Auto decompression — Automatically "opens" exhaust valve to reduce compression for easier starting

EPA Emission Engine Life Rating — The EF5500DE and EF5500D meet the strictest environmental standards - EPA and CARB

Ground Fault Interrupter (G.F.I.) — If the system senses a leak to "ground," it automatically cuts off power to help prevent injuries

Fuel gauge — Lets operator monitor how much fuel is left

Tool kit — Makes service easier

AVAILABLE ACCESSORIES & OPTIONS:

Wired Remote Kit — Features a 33-foot cord with remote starter switch

Yamaha Extended Service — Additional 1, 2 or 3 years of Y.E.S. is available

SPECIFICATIONS:

Type Dual voltage, Brushless, AC Generator

Maximum AC Output 5500 watts

Rated AC Output 4500 watts

Rated / Maximum AC Rated / Maxim

Current

Rated / Maximum AC Current 36.0 / 44.0 amps @

120V - 18.75 / 22.9 amps @ 240V

EngineMZ360Displacement358ccOverall Length31.5 inOverall Width28.4 in

Overall Height 29.1 in (handle down)

Dry Weight D = 221.7 lb, DE = 243.7 lb

Fuel Tank Capacity 6.9 ga
Continuous Operation 9.0 hr

at Rated Load

Noise Level 74.1 dBA

Warranty 3 Years Limited Warranty

Color EF5500DE; EF5500D

^{***} Wet weight includes the vehicle with all standard equipment and all fluids, including oil, coolant (as applicable) and a full tank of fuel. It does not include the weight of options or accessories. Wet weight is useful in making real-world comparisons with other models.